

KEW 2300R - AC/DC Fork Current Tester

100A AC/DC Fork Current Tester

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [KYORITSU](#)

Description

- True RMS reading is an essential feature for accurate measurement.
- “Non Contact” voltage function indicates the presence of AC voltage by warning the user with an audible signal.
- Set the DC current range to zero in one touch with the Zero Adjust function.

Specification:

Current measurement	AC A 0 to 100.0A $\pm 2.0\%$ rdg ± 5 dgt (50/60Hz) DC A 0 to $\pm 100.0A \pm 2.0\%$ rdg ± 5 dgt
Crest factor	2.5
Non contact voltage	Detect AC voltage without contacting with socket wire During voltage detection, "Hi" flashes and a buzzer sounds
Maximum digit	1,049
Conductor size	Max $\varnothing 10$ mm
Safety Standard	IEC 61010-1 CAT III 300V Pollution degree 2
Power source	R03 (AAA) $\times 2$ (Auto power off: approx.10 minutes) *Continuous measuring time: AC A approx. 46 hours DC A approx. 52 hours
Dimensions	161.3(L) $\times$ 40.2(W) $\times$ 30.3(D)mm
Weight	110g (with batteries)
Included Accessories	9113 (Carrying Case) R03 (AAA) $\times 2$ Instruction Manual