

KEW 2433 - Leakage Clampmeter

KEW 2433 - Leakage Clamp Meters

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [KYORITSU](#)

Description

Clampmeter: KEW 2433 - Leakage Clampmeter

- Frequency Selector Switch to eliminate the effect of harmonics.
- Three AC current ranges:40mA/400mA/400A.
- Resolution 0.01mA.

Specification:

AC A (50/60Hz)	40/400mA/400A ±1%rdg±5dgt (40/400mA) ±1%rdg±5dgt (0 - 350A) ±2%rdg (350.1 - 399.9A)
AC A (WIDE)	40/400mA/400A ±2.5%rdg±10dgt [20Hz - 1kHz] (40/400mA) ±2.5%rdg±10dgt [40Hz - 1kHz] (0 - 350A) ±5%rdg [40Hz - 1kHz] (350.1 - 399.9A)
Maximum circuit voltage	600V AC/DC (between line/neutral) 300V AC/DC (against earth)
Conductor size	Ø40mm max.
Frequency response	20Hz - 1kHz (40Hz - 1kHz:400A)
Effect of External Stray Magnetic Field	10mA AC approx. in proximity to a 15mm-dia conductor carrying 100A AC
Safety Standard	IEC 61010-1 CAT III 300V Pollution Degree 2 IEC 61010-2-032
Response Time	Approx. 2 seconds
Power source	Two R03 or equivalent (DC1.5V) batteries
Dimensions	185(L) × 81(W) × 32(D)mm
Weight	270g approx.
Included Accessories	9097 (Carrying Case) R03 (1.5V) × 2 Instruction Manual